

264 Mechanic St LEBANON, NH 03766 603- 448-5580

77 Route 11 SUNAPEE, NH 03782 603-863-3886

www.splashme.com

Recommended Weekly Maintenance: 10,000 gallon pool Adjust amounts based on your gallons.

- 1. Add water if needed
- 2. Vacuum the pool if necessary
- 3. Empty skimmer basket/s if they are in
- 4. Empty debris from pump basket & lube pump lid O'ring if needed
- **5.** Check filter pressure gauge, if pressure has risen 3 5 lbs. above clean beginning pressure, backwash & rinse the filter if it's a Sand Filter / clean cartridges if Cartridge Filter / recharge if D.E. Filter
- 6. Check chlorinator and add ProTeam 3" High Tech Tabs if needed, should have 3-4
- 7. Test pool water... maintain these levels; <u>chlorine 1 3 ppm</u>, <u>pH 7.4 7.8</u>, <u>alkalinity 80 -120 ppm</u>, <u>calcium hardness 200 250 ppm</u> and <u>cyanuric acid</u> (<u>chlorine stabilizer/ UV shield) 30 50 ppm</u>
 - If any of these are not in good range, adjust to bring into proper balance
- **8.** Shock the pool using 1bag ProTeam Power 73 fast dissolving granular Chlorine Shock **or** 1 gallon premium liquid Chlorine Shock
- *** Pools with Nature2 systems should maintain .6 to 1 ppm chlorine and shock with ProTeam Shock & Swim Non-chlorine oxidizer.
- **9.** Add 4 oz. ProTeam Microfloc non foaming algae preventer.
- **10.** Every other week or when adding water, add 4 oz. of ProTeam Metal Magic
- **11.** Add ProTeam Alkalinity Up if needed, to maintain 110 120 ppm
- **12.** After all chemicals are added clean the tile line with ProTeam Tile & Vinyl Cleaner, brush the pool stairs, walls & floor to main drain
- 13. Skim pool surface if needed
- **14.** Wait 1 hour before using the pool if shocking with chlorine, 15 minutes if using Shock & Swim non-chlorine shock or do the above procedure after pool use is done for the day
 - *Once a month bring a water sample to All Seasons Pool & Spa to have all base chemicals tested

Enjoy Your Pool!